

## Elcometer Blast Hose Quick Couplings



Designed for increased safety and a prolonged lifespan, the Elcometer **Blast Hose Quick Couplings** securely attach to the end of the blast hose creating a solid connection and a consistent flow.



### Cast Iron Quick Hose Coupling

Elcometer cast iron quick hose couplings are supplied with safety clips, gasket and coupling screws and are ideal for use up to 15bar (174psi) working pressure.

#### Part Numbers

Part Number	For Blast Hose Internal Diameter (ID)	For Blast Hose Outside Diameter (OD)	Elcometer Blast Hose
<b>SQC-13</b>	13mm (½")	28mm (1⅛")	BH13
<b>SQC-25</b>	25mm (1")	38mm (1½")	BH25
<b>SQC-32</b>	32mm (1¼")	48mm (1⅞")	BH32 & BH32X
<b>SQC-32L</b>	32mm (1¼")	48mm (1⅞")	BH32 & BH32X
<b>SQC-38</b>	38mm (1½")	55mm (2⅜")	BH38 & BH38X



### Nylon<sup>1</sup> Quick Hose Coupling

Elcometer nylon quick hose couplings are supplied with springlock safety clips, gasket and coupling screws. Nylon hose couplings are not recommended for use above 12bar (174 psi) working pressure.

#### Part Numbers

Part Number	For Blast Hose Internal Diameter (ID)	For Blast Hose Outside Diameter (OD)	Elcometer Blast Hose
<b>NQC-19<sup>2</sup></b>	19mm (¾")	34mm (1⅜")	BH19
<b>NQC-25<sup>2</sup></b>	25mm (1")	38mm (1½")	BH25
<b>NQC-32<sup>3</sup></b>	32mm (1¼")	48mm (1⅞")	BH32 & BH32X
<b>NQC-38<sup>3</sup></b>	38mm (1½")	56mm (2⅜")	BH38 & BH38X



Replacement Nylon Coupling Safety Clip



Replacement Cast Iron Coupling Safety Clip

#### Spare Parts

Part Number	Description
<b>MT28723</b>	Coupling Screws (x10) - for BH13 Nozzle Holders and Quick Hose Couplings
<b>MT28724</b>	Coupling Screws (x10) - for BH19+ Nozzle Holder and Quick Hose Couplings
<b>MT29495-2</b>	Gasket (x5) - for SQC-25+ Quick Hose Coupling
<b>MT29495-1</b>	Gasket (x5) - for SQC-13 Quick Hose Coupling
<b>MT29495-5</b>	Gasket (x5) - for NQC-19 Quick Hose Coupling
<b>MT29495-4</b>	Gasket (x5) - for NQC-25 Quick Hose Coupling
<b>MT29495-3</b>	Gasket (x5) - for NQC-32 & NQC-38 Quick Hose Coupling
<b>MT28890</b>	Replacement Cast Iron Coupling Safety Clip (x10)
<b>MT27880</b>	Replacement Nylon Coupling Safety Clip (x10)

<sup>1</sup> A nylon quick hose coupling is not available for 13mm ID hose and are not recommended for use above 12bar (174 psi) working pressure

<sup>2</sup> Supplied with 4 x coupling screws, springlock & gasket

<sup>3</sup> Supplied with 8 x coupling screw, springlock & gasket